

ACCESSORY	DESCRIPTION	PART NUMBER	
Fiberglass Adhesive Tape	Pressure sensitive fiberglass adhesive tape. Used to secure heating cable to pipe.	PSAT36 (.5" x 36yd.), (1.27cm x 32.9M)	Temp Limit 350°F (176°C)
Aluminum Adhesive Tape	Helps to isolate the cable from the insulation and provides intimate contact with pipes, tanks, and plates.	AAT260 (2" x 180'), (5.08cm x 54.9M) AAT2180 (2" x 180'), (5.08cm x 54.9M) AAT3180 (3" x 180'), (7.62cm x 54.9M)	Temp Limit 350°F (176°C) 600°F (315°C) 600°F (315°C)
Pipe straps	Stainless steel pipe straps used to secure pipe standoff to pipe.	BPSCAB032 BPSCAB040 BPSCAB052 BPSCAB060 BPSCAB072 BPSCAB080 BPSCAB096 BPSCAB128	Pipe OD 1.5" (3.8 cm) 2.0" (5.1 cm) 2.5" (6.4 cm) 3.5" (8.9 cm) 4".0 (10.2 cm) 4.5" (11.4 cm) 5.5" (14.0 cm) 5.6" (14.3 cm)
Caution Labels	Electrical heat trace warning label. Required by code for every 10 feet of pipe.	BCLCAB	
Heat conductive putty	Used to fill voids between cable and pipe surface.	HCP 1 (1 lb.) HCP 3 (3 lb.)	
Junction Box:	Single or dual hub with cover. 1" NPT thread.	JBACAB 001 (Single Hub) JBACAB 002 (Double Hub)	
Pipe Standoff	One cast aluminum fitting with 1" NPT thread.	PSOCAB010	
RTV	Silicone sealant (3 oz.) used to seal lead pouches, end pouches, and pipe standoffs.	RTV3.0	
Monitor Light Kit	Provides a continuity check at the termination end of a cable circuit.	MLK1 001 (120V single Hub) MLK2 001 (240V single Hub) MLK1 002 (120V Double Hub) MLK2 002 (240V Double Hub)	
Monitor Light Bulbs	Replacement bulbs for the monitor light kits.	MLBCAB 001 (120V Bulb) MLBCAB 002 (240V Bulb)	
Reducer	Adapts .75" NPT male to 1" NPT female.	BPRCAB 010	